



**ALL ACCESS
EQUIPMENT**

CMC MODEL

60F



TECHNICAL DATA SPECSHEET





60F

UNIQUE FEATURES



- Only 31" wide when retracted in travel mode
- Up to 31' 10" of lateral side reach
- 60' of vertical reach
- Honda Motor GX390 gas engine
- Fixed undercarriage with black rubber tracks
- Fixed two-man aluminum basket (43" x 27" x 55") with rounded corners equipped with quick-release system & wheels
- High-pressure air/water hose in basket
- 12V Electrical socket in basket
- 120V Plug-in electric motor
- Outrigger piston protective covers
- Led display for error code detection
- Fast proportional hydraulic controls
- Proportional travel mode with wired remote control
- 12 month warranty
- Standard painting (RAL 3000)



Have questions? Get in touch with us at:
Office: (978) 712-4950
info@allaccessequipment.com
www.allaccessequipment.com



60F

TECHNICAL SPECIFICATIONS // DIMENSIONS



A	Basket height (basket is removable, variations available)	43"
B	Basket width	27"
C	Basket length	55"
D	Total length (with basket)	15' 11"
E	Length without basket	13' 5"
F	Height in transport position	78"
G	Total width (without basket)	31"
H	Free height from the ground	13"
I	Tracks (L x W x H)	50" x 7" x 13"
J	Outrigger spread length	12' 3"
K	Outrigger spread width	10' 2"
O	Outrigger foot diameter	7"
	Maximum working height	60'
	Maximum side reach with 485 lbs	23' 7"
	Maximum side reach with 176 lbs	31' 10"
	Maximum weight load with standard basket	485 lbs
	Moveable Jib articulating range	90°
	Turret rotation range	+/-356° (non-continuous)
	Basket rotation range	+/- 90° (optional*)
P	Maximum slope to stabilize (deployment)	17° (31%)
	Height / Width tracks adjustment (optional)	31" - 46"
W	Maximum slope approach angle / slope	28° (53%)
X	Gradeability -- max. travel angle / slope	37° (75%)
	Maximum crawler travel speed	1.5 mph

WEIGHT	
Total weight	5,269 lbs

POWER	
Honda GX390 gas engine	11.7 HP
120V 20A plug in electric motor (optional)	
Lithium ion batteries (optional)	





